



Rack Mounted Energy Storage Battery

Dust cover(optional)

Dustproof, no cable leakage, more safer and beautiful appearance.

Touchscreen(optional)

Easier and quicker reading of data.

Compatibility

Tier 1 Inverter Compatibility

Safety

Multi-protection from self developed BMS

Easy to Scale Up

Be workable to be parallel based on 51.2V

Efficient Power Cost

Long cycle life and superior performance

Dawnice MODULE INTRODUCTION

SPECIFICATIONS				
Model (High voltage)	HZEB-HCT-86/6S	HZEB-HCT-100/7S	HZEB-HCT-172/12S	HZEB-HCT-200/14S
Nominal Voltage(V)	307.2V	358.4V	512.0V	716.8V
Cell mode/Configuration	3.2V280Ah/16S1P			
Capacity(Ah) Cell	280Ah			
Rated Energy(kWh)	86.02kWh	100.35kWh	172.03kWh	200.70kWh
Max.Charge/Discharge Current(A)	140A			
Voltage Range(Vdc)	268.8~345.6V	313.6~403.2V	573.6~619.2V	627.2~806.4V
Communication	Modbus RTU			
Cycle Life	≥6000Cycles@25°C,80%DOD			
Design Life	≥15 Years(Cycle Life≥15Years (25°C))			
MECHANICAL SPECIFICATIONS				
Weight(kg)	850kg	960kg	1650kg	1920kg
Dimension(L/W/H)(mm)	1100*792*1218mm	1100*792*1218mm	1100*792*1974mm	1100*792*2226mm
IP Grade	IP20			
SECURITY AND CERTIFICATIONS				
Safety(Pack)	UN38.3,MSDS,IEC62619(CB),CE-EMC			
Safety(Cell)	UN38.3,MSDS,IEC62619,CE,UL1973,UL2054			
Protection	Short- circuit protection/overcurrent protection/over-temperature protection			
ENVIRONMENTAL SPECIFICATIONS				
Operating Temperature(°C)	Charge 0°C~50°C; Discharge -10°C~ 50°C			
Working Altitude(m)	≤2000m			
Humidity	≤95% (Non-condensing)			
Warranty	10 years			

Text and images correspond to the current state of technology at the time of printing, subject to modifications.All information is without guarantee in spite of careful editing-liability excluded

